



SOLCON 80R LT – HEAVY DUTY DEGREASER WITH AN EXTRA MARGIN OF SAFETY

WHAT SOLCON 80R LT DOES

SOLCON 80R LT IS A POWERFUL LIQUID DEGREASER, FORMULATED FROM SPECIAL SOLVENTS, EMULSIFIERS AND WETTING AGENTS. SOLCON 80R LT IS PHOSPHATE FREE AND COMBINES MAXIMUM DEGREASING EFFECTIVENESS WITH MINIMUM HAZARD.

WHY IS SOLCON 80R LT BETTER?

SOLCON 80R LT REMOVES AN UNUSUALLY LARGE NUMBER OF UNRELATED COMPOUNDS. A FEW EXAMPLES FOLLOW:

- HEAVY FUEL AND DIESEL OILS
- CARBON STAINS
- PRESERVATIVE COATINGS
- PACKING GREASE
- ASPHALT, TAR
- RESINS
- PRINTERS' INK
- BODY GREASE FILMS FROM STALL SHOWERS, ETC.

WITH THIS WIDE RANGE OF EFFICACY SOLCON 80R LT CAN BE EMPLOYED BY A MANY INDUSTRIES TO PERFORM A SAFE, ECONOMICAL, LABOUR-SAVING CLEANING OR DEGREASING OPERATION.

SOLCON 80R LT IS SAFER TO USE

SOLCON 80R LT IS NON-FLAMMABLE AND CAUSTIC FREE. IT GIVES OFF NO OVERPOWERING OR HAZARDOUS FUMES. UNLIKE CHLORINATED SOLVENTS, SOLCON 80R LT IS NOT HIGHLY VOLATILE. ITS SOLVENTS EVAPORATE SLOWLY, GIVING OFF ONLY MILD VAPOURS. AT ROOM TEMPERATURES THERE IS VERY LITTLE EVAPORATION.



WHERE TO USE SOLCON 80R LT

- MACHINE TOOLS
- VEHICLE ENGINES AND CHASSIS
- CIVIL ENGINEERING PLANT
- PRINTING MACHINERY
- OILY GARAGE AND ENGINEERING SHOP FLOORS
- OIL FUEL TANKS, PIPELINES, BURNER EQUIPMENT
- MINING EQUIPMENT
- AGRICULTURAL PLANT AND MACHINERY

HOW TO USE SOLCON 80R LT

GENERAL CLEANING AND DEGREASING

DILUTE WITH 5 TO 10 PARTS OF WATER, ALTHOUGH FOR SOME LIGHT DUTY APPLICATIONS, IT MAY BE DILUTED WITH UP TO 40 PARTS OF WATER. EITHER FRESH OR SEA WATER IS EQUALLY SUITABLE.

FOR REMOVAL OF HEAVY, THICK, DRIED OR SEMI-CARBONISED SOILS

SOLCON 80R LT SHOULD BE USED UNDILUTED AND A PERIOD OF SOAKING TIME ALLOWED IF NECESSARY.

TEMPERATURE

SOLCON 80R LT, WHETHER IN THE CONCENTRATED OR THE DILUTED FORM, CAN BE USED COLD OR HOT (UP TO 82.2°C). HIGHER TEMPERATURES ARE NOT RECOMMENDED DUE TO LOSSES OF THE ACTIVE SOLVENT.

SOLCON 80R LT CAN BE USED IN SEVERAL WAYS, DEPENDING UPON THE APPLICATION AND EQUIPMENT AVAILABLE.

HOT OR COLD TANK FOR SOAKING PARTS.

WIPE APPLICATION WITH BRUSH OR CLOTH FOR MACHINERY AND EQUIPMENT.

PRESSURE SPRAYING LARGE STRUCTURES OR EQUIPMENT.

HOW TO USE SOLCON 80R LT

SOLCON 80R LT IS EXCELLENT FOR REMOVING OIL SPILLS AND FOR CLEANING EQUIPEMT, IN ANY OF THE ABOVE METHODS OF APPLICATION.



SOLCON 80R LT ACTS BY PENETRATION. THE CHEMICAL DOES THE WORK AND VERY LITTLE MANUAL EFFORT IS REQUIRED. IT MUST BE ALLOWED SUFFICIENT TIME TO CUT THROUGH THE ACCUMULATION OF SOIL, THE AMOUNT OF TIME DEPENDING ON THE THICKNESS OF THE SOIL. THE CLEANED PART OR SURFACE CAN BE RINSED WITH CLEAR WATER – PREFERABLY UNDER PRESSURE FROM A PLAIN WATER HOSE OR STEAM CLEANER. IT CAN ALSO BE RINSED WITH SOLVENTS OR SIMPLY WIPED DOWN WITH A DRY CLOTH.

HEALTH AND SAFETY

SEE SEPARATE SAFETY DATA SHEET

THE INFORMATION CONTAINED IN THIS DATA SHEET IS ACCURATE TO THE BEST OF OUR KNOWLEDGE AND BELIEF. NO WARRANTY IS, HOWEVER, GIVEN OR IMPLIED. CONSULT AGMA LTD CONCERNING ALL NON-STANDARD APPLICATIONS.

ISSUE NO. 1-03/25